### FLIGHT SUMMARY REPORT

Flight Number: 98-133

Calendar/Julian Date: 23 September 1998 • 266

Sensor Package: Wild Heerbrugg RC-10

Dual Hycon HR-732

Area(s) Covered: Los Padres National Forest

Sequoia National Forest

**Investigator(s):** Functional Sensor Flight Aircraft #: 809

#### **SENSOR DATA**

Accession #: 05311 05312 05313

Sensor ID #: 076 019 020

Sensor Type: RC-10 HR-732 HR-732

12" 24" 24" Focal Length:

> 304.89 mm 609 mm 609 mm

Film Type: Aerochrome IR Aerochrome MS Panatomic X

SO-134 2448 II Aerographic II, EK 2412

Filtration: Wratten 12 None Wratten 12

**Spectral Band:** 510-900 nm 400-700 nm 510-700 nm

f Stop: 11 16 18

**Shutter Speed:** 1/275 1/250 1/250

# of Frames: 38 122 122

% Overlap: 60 60 60

Excellent **Quality:** Excellent Good

Remarks: Add 2 seconds Add 6 seconds Add 6 seconds

for correct UTC for correct UTC for correct UTC

### **Airborne Science and Applications Program**

The Airborne Science Program at NASA's Dryden Flight Research Center, Edwards, California, operates two ER-2 high altitude aircraft in support of NASA earth science research. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

### **Camera Systems**

Various camera systems and films are used for photographic data collection. Film types include high definition color infrared, natural color, and black and white emulsions. Available photographic systems are as follows:

- Wild-Heerbrugg RC-10 metric mapping camera
  - 9 x 9 inch film format
  - 6 inch focal length lens provides area coverage of 16 x 16 nautical miles from 65,000 feet
  - 12 inch focal length lens provides area coverage of 8 x 8 nautical miles from 65,000 feet
- Hycon HR-732 large scale mapping camera
  - 9 x 18 inch film format
  - 24 inch focal length lens provides area coverage of 4 x 8 nautical miles from 65.000 feet
- IRIS II Panoramic camera
  - 4.5 x 34.7 inch film format
  - 24 inch focal length lens
  - 90 degree field of view provides area coverage of 2 x 21.4 nautical miles from 65,000 feet

### **Data Availability**

The U.S. Geological Survey's EROS Data Center at Sioux Falls, South Dakota serves as the archive and product distribution facility for Airborne Science Program aircraft acquired photographic and digital imagery. The photographic archive consists of photography acquired by the program from 1971 to April 1996. For information regarding photography and digital data (including areas of coverage, products, and product costs) contact EROS Data Center, Customer Services, Sioux Falls, South Dakota 57198 (Telephone: 605-594-6151).

As of April 1996 the EROS Data Center no longer receives an archive copy of newly acquired Airborne Science Program photography. Original photography is archived with the Airborne Sensor Facility at Ames Research Center. A user copy of the photography is provided to the principal investigators for each flight. Principal investigators are cited on the first page of their respective flight summary reports. For information regarding photography acquired from April 1996 to the present contact the Airborne Sensor Facility as follows:

### Flight Documentation and Data Archive Searches

The following is the web site for flight documentation as published by the Airborne Sensor Facility at NASA Ames Research Center: http://asapdata.arc.nasa.gov/er-2fsr.html

Additional information regarding flight documentation to include data archive searches, data availability, sensor parameters, and areas of coverage may be obtained from the following: Airborne Sensor Facility, MS 240-6, NASA Ames Research Center, Moffett Field, CA 94035-1000, Telephone: 650.604.6252 (FAX 4987).

# CAMERA FLIGHT LINE DATA FLIGHT NO. 98-133

Accession # 05311

Sensor # 076

Check	Frame	Time (GMT-hr, min, sec)		Altitude, MSL	
Points	Numbers	START	END	feet/meters	Cloud Cover/Remarks
A - B	0103-0140	18:38:58	18:56:22	65589/19992	Cloud Cover/Remarks  50-90% cumulus (frames 0103-0121); 20- 40% cumulus (frames 0122-0129); minor- 10% cumulus (frames 0130-0133); 10-30% cumulus (frames 0139-0140)

# CAMERA FLIGHT LINE DATA FLIGHT NO. 98-133

Accession # 05312

Sensor # 019

Check	Frame	Time (GMT-hr, min, sec)		Altitude, MSL	
Points	Numbers	START	END	feet/meters	Cloud Cover/Remarks
A - B	0001-0074	18:38:30	18:56:19	65585/19990	50-90% cumulus (frames 0001-0038); 20- 40% cumulus (frames 0039-0052); minor- 10% cumulus (frames 0053-0059); 10-30% cumulus (frames 0072-0074)
C - D	0075-0093	18:59:39	19:04:02	64926/19789	Minor-10% cumulus (frames 0075-0079, and 0082-0090)
E - F	0094-0103	19:15:56	19:18:07	64370/19620	Minor-10% cumulus (frames 0102-0103)
G - H	0104-0112	19:22:33	19:24:29	64156/19555	Minor-10% cumulus (frames 0106-0112)
I - J	0113-0122	19:34:53	19:37:04	64410/19632	Minor cumulus (frame 0113)

# CAMERA FLIGHT LINE DATA FLIGHT NO. 98-133

Accession # 05313

Sensor # 020

Check	Frame	Time (GMT-hr, min, sec)		Altitude, MSL	
Points	Numbers	START	END	feet/meters	Cloud Cover/Remarks
A - B	0001-0074	18:38:30	18:56:19	65585/19990	50-90% cumulus (frames 0001-0038); 20- 40% cumulus (frames 0039-0052); minor- 10% cumulus (frames 0053-0059); 10-30% cumulus (frames 0072-0074)
C - D	0075-0093	18:59:39	19:04:02	64926/19789	Minor-10% cumulus (frames 0075-0079 and 0082-0090)
E - F	0094-0103	19:15:56	19:18:07	64370/19620	Minor-10% cumulus (frames 0102-0103)
G - H	0104-0112	19:22:33	19:24:29	64156/19555	Minor-10% cumulus (frames 0106-0112)
I - J	0113-0122	19:34:53	19:37:04	64410/19632	Minor cumulus (frame 0113)





